

Big Jim

POST DRIVERS



Proudly Made in Canada

FEATURES & BENEFITS



The Mast tilts in and out as well as forward and back for post leveling on uneven ground.



The Mast travels out 16 inches and the tongue travels out 24 inches. This enables the operator to accurately place posts without moving the entire machine.



The Mast lifts hydraulically 24 inches. This allows a fast change from 8 to 10 foot posts. This feature also allows a longer hammer stroke for starting 8 foot posts.



The Hammer and Mast in fully raised position reaches a height of 11' 6" from the hammer to the ground.



Large 15 Gallon Oil Reservoir



Post Carrier Rack



Joystick Control Valve



Standard Round Post Hugger



The BJ740-T and BJ740-T Plus model can be ordered with an *optional* round/square combination hugger. Both the round and square hugger are made of steel. The hugger swings out of the way for working on existing fence lines.

SAFETY FEATURES



Forward/Backward Tilt Stop Tab



Transport Lock Chain on Tilt Assembly



Standard Hydraulic Stabilizer Arm on Plus Model **ONLY**; Provides enhanced stability when in outward and raised positions.



Outward Tilt Stop Cable

All Big Jim Post Drivers come with built in safety features to prevent injury in the event of a sudden hydraulic failure. All units come complete with a DOT approved safety chain on tongue.

SPECIFICATIONS

Model	BJ740-3PH/SS	BJ740-T	BJ740-T PLUS
Hammer Weight	740 lbs.	740 lbs.	740 lbs.
Counter Weight	N/A	979 lbs.	1,306 lbs.
Total Weight	1,697 lbs.	3,748 lbs.	4,440 lbs.
Hammer Maximum Height Lower Mount	9' 6"	9' 6"	9' 6" – 11' 6"
Hammer Maximum Height Upper Mount	11' 6"	11' 6"	11' 6" – 13' 6"
Hammer Minimum Height Lower Mount	4' 2"	4' 2"	4' 2" – 6' 2"
Hammer Minimum Height Upper Mount	6' 2"	6' 2"	6' 2" – 8' 2"
Hammer Stroke	64"	64"	64"
Overall Width	42"	84"	90"
Overall Length	48"	108"	108"
Transport Height	100"	100"	104"
Mast Tilt Forward/Backward	18°	18°	18°
Mass Tilt In/Out	12°	12°	12°
Mast Vertical Lift	N/A	N/A	24"
Mast Horizontal Travel	N/A	16"	16"
Tongue Travel	N/A	16"	24"
Tires	N/A	9.5L-15 8PR	9.5L-15 8PR
Wheels	N/A	6 Bolt Ag	6 Bolt Ag
Spindles and Hubs	N/A	5000 lb.	5000 lb.
Reservoir	N/A	15 Gallon	15 Gallon
Drive System	N/A	13 HP Honda	13 HP Honda
Frame	6" x 3" 1/4"	6" x 3" 1/4"	6" x 3" x 1/4"

Represented By:



5808 Hwy #9
 Harriston, Ontario, N0G 1Z0
 Ph: 519-338-2923, Fax: 519-338-2756
 Email: sales@harcoag.ca
 www.harcoag.ca

Dealer: