



MORE IMPROVEMENT



REAR BLADES



NVHL SERIES



EXTRA HEAVY DUTY SERIES



REGULAR DUTY SERIES



T/TL/F SERIES



NVHA SERIES

www.bison.com.mx
01 800 52 BISON



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905
Jesús María, Aguascalientes, México
Tel. (449) 92-BISON / Fax. (449) 922 4767

* 360 Swing Angle
Parking Stand Included



NVHL SERIES *



SPECIFICATIONS		NVHL-240-XHD	NVHL-270-XHD	NVHL-300-XHD
Moldboard Width	ft	8	9	10
Approximate weight	lb	1240*/1450**	1280*/1490**	1320*/1530**
King pin diameter		4		
Moldboard height & thickness	in	19" x 5/16" (whit full box frame)		
Cutting edge	in	1/2" x 6"		
Maximum tractor hp	hp	160 (2WD) & 145 (4WD)		
Hitch	in	3 - point cat. II, II quick hitch, III		
Swing angle		0 to 45° left or right (manual or hydraulic) ¹		
Offset adjustment		0 to 32 3/8 left or right (manual or hydraulic) ¹		
Tilt adjustment		0 to 12° up or down (manua or hydraulic) ³		

SPECIFICATIONS		NVH 240-XHD	NVH 270-XHD	NVH 300-XHD	NHVH 212-XHD	NHVH 242-XHD	NHVH 272-XHD	NHVH 302-XHD
Moldboard width	ft	8	9	10	7	8	9	10
Approximate weight	lb	926	1,020	1,069	1060 (manual)	1139 (manual)	1240 (manual)	1300 (manual)
king pin diameter	in				1162 (hyd.)	1241 (hyd.)	1342 (hyd.)	1402 (hyd.)
Moldboard height & thickness	in	3			3			
Cutting edge		19" x 5/16" 1/2" x 6" high carbon-steel blade, reversible, interchangeable			19" x 5/16" 1/2" x 6" high carbon-steel blade, reversible, interchangeable			
Maximum tractor hp	hp	120 (2WD) & 110 (4WD)			120 (2WD) & 110 (4WD)			
Hitch		3 - point category II and II quick hitch ⁴			3 - point category II and II quick hitch ⁴			
Swing angle		Forward or reverse positions, 3, up to 45° left or right			Forward or reverse positions, 0° to 45° left or right (hydraulic) ^{1,3}			
Offset adjustment	in	2, up to 18 left or right (manual) 0 a 19° left or right (hydraulic) ¹			0 to 19 left or right (hydraulic) ^{1,3}			
Tilt adjustment		3, up to 23° up or down			0° to 15° up or down (hydraulic) ^{2,3}			

EXTRA HEAVY DUTY SERIES *



SPECIFICATIONS		NVH-210	NVH-240	NVH-270
Moldboard width	ft	7	8	9
Approximate weight	lb	677	706	800
King pin diameter	in	3		
Moldboard height & thickness	in	18 x 1/4"		
Cutting edge		1/2" x 6" high carbon-steel blade, reversible, interchangeable		
Maximum tractor hp	hp	65	80	
Hitch		3 - point category II		
Swing angle		15°, 30° and 45°, left or right, 3 forward and 3 reverse positions		
Offset adjustment	in	9 or 18 left or right (manual or hydraulic) ¹		
Tilt adjustment		7.5°, 15°, 22.5° up or down		

REGULAR DUTY SERIES *



SPECIFICATIONS		NVHF-152	NVHF-182	NVHF-212	NVH-120-T	NVH-150-T	NVH-180-T(LT)	NVH-210-T	NVH-240-T
Moldboard width	ft	5	6	7	4	5	6	7	8
Approximate weight	lb	250	280	310	345	375	404 (372)	433	462
Moldboard height & thickness	in	12 1/2" x 1/4"			2 5/8"				
Cutting edge	in	1/2" x 6" high carbon-steel blade, reversible, interchangeable			17" x 1/4" 1/2" x 6" high carbon-steel blade (3/8" x 4" spring steel blade), reversible, interchangeable				
Maximum tractor hp	hp	55 (2WD) & 50 (4WD)			65 (2WD) & 60 (4WD)				
Hitch		3 - point category I and I quick hitch ¹			3 - point category I and I quick hitch ¹				
Swing angle	in	20°, 40° and 60°, left or right, 3 forward and 3 reverse positions			18°, 35° and 53°, left or right, 3 forward and 3 reverse positions				
Offset adjustment	°	0 to 12 left or right			6 or 12 left or right				
Tilt adjustment		0° to 20° up or down			6 left or right 7.5°, 15°, 22.5° and 30° up or down				

T/TL/F SERIES *



NVHA SERIES *



SPECIFICATIONS		NVHA-180	NVHA-210	NVHA-240
Moldboard width	ft	6	7	8
Approximate weight	lb	330	366	391
Angle, tilt & offset	in	Manual or Hydraulically adjusted angle and manually tilt and offset		
Moldboard height & thickness	in	15" height, 1/4" thickness		
Cutting edge		1/2" x 6" reversible		
Maximum tractor hp	hp	60 hp (4WD)		
Hitch		3 Point CAT I		
Moldboard upper edge		Full Bend		
Offset adjustment		6" or 12" left or right		
Tilt adjustment	in	0 to 20 degrees up or down		