



# PULL TYPE SNOWBLOWERS PERFORMANCE SERIES

### **SPECIFICATIONS**

Models	SB54PT-P	SB60PT-P	SB68PT-P	SB72PT-P	SB78PT-P	SB87PT-P	SB97PT-P
HP (Rec.)	25 HP	25 HP	35 HP	35 HP	50 HP	60 HP	60 HP
<b>Cutting Width</b>	54"	60"	68"	72"	78"	87"	97"
Cutting Edge	Bolt On (½ x 4)						
Auger Diam.	14"	14"	14"	14"	15"	19"	19"
Fan Diam.	18"	18"	21"	21"	23"	27"	27"
Chute Diam.	8"	8"	10"	10"	10"	12"	12"
Chute Rotation	Must select either Manual (opt.) or Hydraulic (opt.) or Electric (opt.)						
Chute Deflector	Manual Std./Opt. 6" cyl.				Manual Std./Opt. 8" cyl.		
Double Hood Deflector	N/A	N/A	Std.	Std.	Std.	Std.	Std.
Main Body Height	23"	23"	23"	23"	26"	28"	28"
3PH Mount	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1 & 2	Cat. 2	Cat. 2
Weight (LBS.)	462	495	671	685	900	1,175	1,260
Tube Size	2 3/8" OD	2 3/8" OD	2 3/8" OD	2 3/8" OD	3 ½" OD	3 ½" OD	3 ½" OD
Flighting Size	1/4 x 2 1/4	1/4 x 2 1/4	1/4 x 2 1/4	1/4 x 2 1/4	1/4 x 2 1/4	5/16 x 2 1/4	5/16 x 2 1/4
Roller Chain Drive	# 50	# 50	# 60 Heavy	# 60 Heavy	# 60 Heavy	# 60 Heavy	# 60 Heavy
Fan Depth	5"	5"	7"	7"	8"	10"	10"
Blades Per Fan	5	5	5	5	5	5	5
Auger Drive Shaft Size	1"	1"	1 1⁄4"	1 1⁄4"	1 1⁄4"	1 1⁄4"	1 1⁄4"
Fan Output Shaft Size	1 3/8"	1 3/8"	1 3/8"	1 3/8"	40mm	40mm	40mm

## **FEATURES**

## Cleans Tight to the Garage Door



5 Blade Impeller



High Tensile Steel Flighting



#### **OPTIONS**

- Hydraulic, manual and electric chute rotators
- Hydraulic chute deflectors
- Tivar contact surfaces

#### **Tivar Wear Parts**

Tivar is a wear resistant plastic that replaces steel cutting edges and bolts onto the skid shoes.

Standard Manual Chute Deflector

Multi-Hinged Deflector

Standard Manual Chute Rotator

[SB68P/T - SB97P/T]

Standard Manual Chute Rotator

[SB54PT & SB60PT]

Optional on Pull Type models, the tivar is gentler when clearing, ideal for interlocking brick and decorative stone.









Skid Shoe

**Cutting Edge**