





1000 RPM PTO Kit

Available for the SELB97D and SEL108D models, this kit allows the PTO of larger tractors to run at 1000 RPM without damaging the standard 540 RPM gearbox. The 1000 RPM Kit also raises the input shaft to allow the PTO shaft to run at a lesser angle on larger tractors increasing the efficiency and life of the driveline components.

Note: features rotation reversal for front mount applications if required.

	SEL48	SEL54	SEL60	SEL68	SEL72
Rec. HP	15	15	20	20	35
Cutting Width	48"	54"	60"	68"	72"
Cutting Edge	3/8 x 1 (Weld-On)	3/8 x 1 (Weld-On)	3/8 x 1 (Weld-On)	3/8 x 1-1/2 (Weld-On)	3/8 x 1-1/2 (Weld-On)
Auger Diam.	12"	14"	14"	14"	14"
Auger Flighting	1/4 x 1-1/2	1/4 x 2-1/4	1/4 x 2-1/4	1/4 x 2-1/4"	1/4 x 2-1/4"
Auger Drive Shaft	1"	1"	1"	1-1/4"	1-1/4"
Auger Tube	2	2-3/8" OD	2-3/8" OD	2-3/8" OD	2-3/8" OD
Fan Diameter	18"	18"	18"	21"	21"
Fan Depth	5"	6"	6"	7"	7"
Fan Output Shaft	1"	1-1/4"	1-1/4"	1-3/8"	1-3/8"
Chute Diameter	7"	8"	8"	9"	9"
Chute Rotation	Man. Or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. Or Hyd. (Opt.)	Man. Or Hyd. (Opt.)
Chute Deflector	Manual	Manual	Manual	Man. Or Hyd. (Opt.)	Man. Or Hyd. (Opt.)
Main Body Height	22"	22"	22"	25"	25"
Roller Chain	#50	#50	#50	#60 Heavy	#60 Heavy
Skid Shoes	1/4 x 1-1/2 Weld -On	3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On
3PH Category	Cat. 1 & Quick Attach	Cat. 1 & Quick Attach	Cat. 1 & Quick Attach	Cat. 1 & Quick Attach	Cat. 1 & Quick Attach
Weight	303 lbs.	366 lbs.	390 lbs.	437 lbs.	485 lbs.
Hyd. Chute Rotator	Opt.	Opt.	Opt.	Opt.	Opt.
Hyd. Chute Deflector Kit	Opt.	Opt.	Opt.	Opt.	Opt.
Elec. Chute Deflector Kit	Opt.	Opt.	Opt.	Opt.	Opt.
1000 RPM Kit	N/A	N/A	N/A	N/A	N/A



Manual Chute Rotator

Manual rotators are standard on all models, except SEL97D and 108D, and can be optionally outfitted on most models where operators can safely reach the adjustment handle.



Chute Deflector

All Select blowers come with a manual pin style deflector allowing a true set it and forget approach to blowing snow.



Four Blade Fan

All Select blowers now feature a standard 4 blade fan. The four blades not only evacuate high volumes of snow quickly, but also feature tighter tolerance to the housing increasing velocity of the snow exiting the chute.



Skid Shoes

Select blowers come equipped with adjustable skid shoes extending the life of the cutting edge and helping to protect surfaces from damage commonly associated with snow removal.



Flighting

To deliver even the heaviest wet snow to the awaiting fan, Select blowers use machine formed hand welded augers made with high tensile steel ribbon flighting to provide strength and durability for years to come.



3PH / Quick Attach

All single auger PTO driven models are built for Category 1 or Category 2 type 3PH. Dual auger PTO driven models are built for Category 2 or Category 3 type 3PH. All models are Quick Attach compatible.

SEL78	SEL87S	SEL87D	SEL97S	SEL97D	SEL108D
50	60	60	75	100	125
78"	87"	87"	97"	97"	108"
3/8 x 2 (Weld-On)	3/8 x 3 (Weld-On)	3/8 x 3 (Weld-On)	3/8 x 3 (Weld-On)	1/2 x 6 (Bolt-On)	1/2 x 6 (Bolt-On)
15"	19"	15" (x2)	19"	19" (x1) and 15" (x1)	19" (x1) and 15" (x1)
1/4 x 2-1/4"	5/16 x 2-1/4	1/4 x 2-1/4	5/16 x 2-1/4	5/16 x 2-1/4	5/16 x 2-1/4
1-1/4"	1-1/4"	1-1/4"	1-1/4"	1-3/4"	1-3/4"
3-1/2" OD	3-1/2" OD	3-1/2" OD	3-1/2" OD Heavy Wall	4-1/2" OD Heavy Wall	4-1/2" OD Heavy Wall
23"	26"	26"	26"	32"	32"
8"	10"	10"	10"	12"	12"
40mm	40mm	40mm	40mm	2"	2"
10"	13"	13"	13"	14"	14"
Man. Or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Hydraulic	Hydraulic
Man. Or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)	Man. or Hyd. (Opt.)
29"	32"	36"	32"	39"	39"
#60 Heavy	#60 Heavy	#60 Heavy	#60 Heavy	#80	#80
3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On	3/8 x 1-1/2 Weld-On	1/2 x 2 Weld-On	1/2 x 2 Weld-On
Cat. 1, 2 & Quick Attach	Cat. 2 & Quick Attach	Cat. 2 & Quick Attach	Cat. 2 & Quick Attach	Cat. 2, 3 & Quick Attach	Cat. 2, 3 & Quick Attach
720 lbs.	885 lbs.	1,082 lbs.	1,005 lbs	1,596 lbs.	1,692 lbs.
Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Opt.	N/A	N/A	N/A	N/A	N/A
N/A	N/A	N/A	N/A	Opt.	Opt.

Skidsteer Blowers

Select Snow Blowers for Skid Steer Loaders feature one piece side plate construction for added strength and rigidity. They also feature an offset chute for better operator vision.

- Hydraulic line check valve prevents reverse rotation and allows the motor to overrun after valve is shut off
- Direct fan drive mounted with 2" bearings
- Heavy duty fan has 5 impeller blades
- Solenoid valve feature allows for use of hydraulic rotator motor and hydraulic deflector cylinder
- Various plug options to match your skidsteer so you can use the controls on the skidsteer



Five Blade Fan



Models	SELSS62	SELSS66	SELSS76	SELSS86	SELSS96
Cutting Edge (Bolt-On)	1/2 x 4	1/2 x 4	1/2 x 4	1/2 x 4	1/2 x 4
Cutting Width	65"	69"	79"	89"	99"
Auger					
Tube	3 1/2" Round				
Flighting	5/16 x 2 1/4				
Auger Diam.	19"				
GPM (min)	14	14	14	23	33
Mounting	Universal Skidsteer Attach				
Chute Rotation	Hydraulic				
Chute Diam.	11"				
Main Body Height	31"				
Chute Deflector (Man/Hyd)	Std/Opt				
Fan Diam.	26"				
Fan Shaft	2" Diam.				
Weight (LBS.)	900	925	950	975	1,025



Authorized Dealer

3950 Steffler Rd., Elmira Ontario, N3B 2Z3
Toll Free: 855-664-2752
Tel.: 519-664-2752
Fax: 519-664-3695
Email: sales@mkmartin.ca
www.mkmartin.ca