



SINGLE SHANK RIPPERS



SINGLE SHANK RIPPERS: **100 Series** is ideal for breaking up hard soil or furrowing cultivated soil by adding the optional 12" furrow shovel. Designed for category 1 tractors up to 25 HP. The 1" x 4" shank is adjustable to 19" length for ripping and 15" length for furrowing. The shank is shear-bolt protected and equipped with a 2" wide, hard-faced replaceable point. **200 Series** is recommended for breaking up compacted soil to increase root growth and yield. This rugged built unit is available with a 1" x 6" x 23" shank and designed for category 1 tractors up to 50 HP. The shank is shear-bolt protected and equipped with a high carbon heat-treated replaceable point. **300 Series** is ideally suited to break-up hard and compacted soil for better water penetration and root growth. This unit is constructed of heavy-duty 4" x 8" x 3/8" tubing and is equipped with a 1" x 27" parabolic shank and designed for category 2 tractors up to 75 HP. The shank is shear-bolt protected and equipped with a high carbon heat-treated replaceable point. Models 102L and 300 are Quick Hitch Compatible.

| Models | 100 | 200 | 300 |
|-----------------------|-----------|----------|----------|
| NO. OF SHANKS | 1 | 1 | 1 |
| FRAME TUBE SIZE | 3" X 3" | 4" X 4" | 4" X 8" |
| SHANK LENGTH | 15" & 19" | 23" | 27" |
| HITCH | Cat. 1 | Cat. 1 | Cat. 2 |
| HP RATING | Up to 25 | Up to 50 | Up to 75 |
| SHEAR-BOLT PROTECTION | Yes | Yes | Yes |
| WEIGHT | 85 | 130 | 240 |
| OPTIONAL 12" FURROWER | Yes | No | No |
| PARKING STANDS | No | Optional | Optional |

Specifications subject to change without notice

Innovative, Rugged & Labor Saving Attachments